

銅ニッケル抵抗線第四種の抵抗及び重量表

線 径 mm	線径許容差 mm	断面積 mm ²	導体抵抗 Ω/m	導体抵抗許容差 %	重 量 g/m
5.00	± 0.07	19.64	0.005091	± 5%	174.8
4.50	"	15.90	0.006290	"	141.6
4.00	± 0.06	12.57	0.007956	"	111.9
3.50	"	9.621	0.01040	"	85.63
3.20	± 0.05	8.042	0.01244	"	71.58
2.90	"	6.605	0.01515	"	58.78
2.60	"	5.309	0.01884	"	47.25
2.30	"	4.155	0.02407	"	36.98
2.00	± 0.04	3.142	0.03183	"	27.97
1.80	"	2.542	0.03929	"	22.66
1.60	± 0.035	2.011	0.04973	"	17.89
1.50	"	1.767	0.05659	"	15.72
1.40	"	1.539	0.06498	± 6%	13.70
1.30	± 0.030	1.327	0.07536	"	11.81
1.20	"	1.131	0.08841	"	10.07
1.10	"	0.9503	0.1052	"	8.457
1.00	± 0.025	0.7854	0.1274	"	6.990
					g/km
0.90	"	0.6362	0.1571	"	5.662
0.85	"	0.5675	0.1762	"	5.052
0.80	"	0.5027	0.1989	"	4.474
0.75	"	0.4418	0.2263	"	3.931
0.70	± 0.02	0.3848	0.2599	"	3.425
0.65	"	0.3318	0.3014	± 7%	2.952
0.60	"	0.2827	0.3538	"	2.516
0.55	"	0.2376	0.4209	"	2.114
0.50	± 0.015	0.1964	0.5091	"	1.748
0.45	"	0.1590	0.6290	"	1.416
0.40	"	0.1257	0.7956	"	1.119
0.35	"	0.09621	1.040	± 8%	856.3
0.32	"	0.08042	1.244	"	715.8
0.29	"	0.06605	1.515	"	587.8
0.26	± 0.01	0.05309	1.884	"	472.5
0.23	"	0.04155	2.407	"	369.8
0.20	"	0.03142	3.183	"	279.7
0.18	± 0.009	0.02545	3.929	± 9%	226.6
0.16	± 0.008	0.02011	4.973	"	178.9
0.15	"	0.01767	5.659	"	157.2
0.14	"	0.01539	6.498	"	137.0
0.13	"	0.01327	7.536	"	118.1
0.12	± 0.006	0.01131	8.841	"	100.7
0.11	"	0.009503	10.52	± 10%	84.57
0.10	± 0.003	0.007854	12.74	"	69.90

※ 固有抵抗は10±1 μ Ω cm